

BRAIDED BUTYL HOSES

DN	NOM. PRESSURE	MAX. PRESSURE	BRAIDING AISI304L	HOSE DIAMETER
DN8	10 BAR	20 BAR	INOX 8x0,18 mm	8x11,2 mm
DN10	10 BAR	20 BAR	INOX 8x0,18 mm	10x14 mm
DN13	10 BAR	18 BAR	INOX 9x0,22 mm	13x17 mm
DN15	10 BAR	16 BAR	INOX 9x0,22 mm	15x19,8 mm
DN20	10 BAR	16 BAR	INOX 12x0,22 mm	19,5x26 mm
DN25	8 BAR	10 BAR	INOX 12x0,22 mm	25x32 mm
DN32	8 BAR	10 BAR	INOX 10x0,25 mm	32x42 mm
DN40	6 BAR	10 BAR	INOX 10x0,25 mm	40x52 mm
DN50	6 BAR	8 BAR	INOX 10x0,25 mm	50x62 mm

CERTIFICATIONS



OXYTIGHT
COOLING
HEATING



SLEEVES AND FITTINGS

DN	SLEEVE DIMENSIONS	BORE DIAMETER FITTINGS
DN10	15,5x16,5x20 mm	7 mm
DN13	20x22x24 mm	10,5 mm
DN15	23x24,4x29 mm	12 mm
DN20	30x32x35 mm	15 mm
DN25	36x38x35 mm	19 mm
DN32	45x47x46 mm	25,5 mm
DN40	55x57x62 mm	32 mm
DN50	67,6x70x57 mm	41 mm

LENGTH NBN EN 13618

LENGTH OF HOSE	TOLERANCE
$L \leq 400$ mm	- 0 mm / + 10 mm
400 mm $< L \leq 1000$ mm	- 0 mm / + 20 mm
1000 mm $< L \leq 2000$ mm	- 0 mm / + 30 mm

